



FEATURES

- ▶ Separate display and transponder unit
- ▶ 7" Touch Screen Display
- ▶ Easy ECDIS interface
- ▶ Software upgradable
- ▶ Collision alarms (tCPA, CPA)

Tron AIS TR-8000

AUTOMATIC IDENTIFICATION SYSTEM
CLASS A



www.jotron.com



▶ Tron AIS TR-8000

AUTOMATIC IDENTIFICATION SYSTEM - CLASS A

Features:

- Separate display and transponder unit
- 7" Touch Screen Display
- Software upgradable
- Compact design for easy installation
- Console or desktop mounting
- Combined Junction-box/transponder
- Display rated to IP54 + Extended temperature (IEC 60945)
- Transponder rated to IP56, + Exposed (IEC 60945)
- Upgradable to be in-land waterways regulation compliant
- Easy ECDIS interface



Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

v.D

www.jotron.com

SPECIFICATIONS

Conforming standards	IMO MSC.74 (69) annex 3; MSC.191(79) ITU-R M.1371-4 IEC 61993-2, IEC 60945 IEC 61162-1/2, IEC 62288 Ed.1
Weight: - TR-8000 Display unit - TR-8000 Transponder unit	1 kg 3,7 kg
Dimensions: - Display unit - WxDxH - Transponder unit - WxDxH	210mm x 83mm x 150,4mm 319mm x 204mm x 77mm
Supply, voltage	10,8 - 31,2 VDC
Power consumption - TR-8000 Display unit: - TR-8000 Transponder unit:	Normal: <12W Max intensity: <20W Receive: <15W Transmit (max): <50W
GPS module	16 channels
Channels, default	2087 (161.975 MHz) 2088 (162.025 MHz)
Channels to be used by National Authorities all in the range of	156 - 162.025 MHz
DSC channel	70 (156.525 MHz)
RF output power	12,5 / 1 W
Interfaces	IEC 61162-1 (RS422-adjustable baudrate: 5 inputs) IEC 61162-2 (RS422-38400 b/s: 2 I/O) RS232-adjustable baurate: 1 I/O LAN (10Base-T Ethernet: 1 I/O)
Data presentation	TR-8000 Display unit Optional ECDIS, ECS, ARPA or PC
Operational temperature range	-25°C to 55°C
Storage temperature range	-30°C to 70°C
STANDARD SUPPLY TR-8000 Transponder unit TR-8000 Display unit GPS antenna w/cable and bracket Flush mounting kit Plug kit Standard bracket mounting kit Product manual	OPTIONAL SUPPLY VHF antenna Combined VHF / GPS antenna Antenna signal splitter Gyro converter AC / DC converter Antenna cables

CONTACT INFORMATION

Jotron AS
P.O.Box 54
3281 Tjodalving
Norway
Tel: +47 33 13 97 00
Fax: +47 33 12 67 80
sales@jotron.com

Jotron UK Ltd.
Crosland Park
Cramlington
NE23 1LA
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd.
19 Loyang Way
Changi Logistics Centre
Rear Office Block 04-26
Singapore 508724
Tel: +65 65426350
Fax: +65 65429415
sales@jotron.com

Jotron USA, Inc.
10645 Richmond Avenue, Suite 170
Houston, TX 77042
USA
Tel: +1 713 268 1061
Fax: +1 713 268 1062
sales@jotron.com